SAFETY DATA SHEET
(in accordance with Regulation (EU) 2020/878)

100041-SPANISH SAGE ESSENTIAL OIL ORGANIC

SECTION 1: IDENTIFICATION OF THE SUBSTANCE/MIXTURE AND OF THE COMPANY/UNDERTAKING.

1.1 Product identifier.

Product Name:	SPANISH SAGE ESSENTIAL OIL ORGANIC
Product Code:	100041
Chemical Name:	Sage oil, Spanish (Salvia lavandifolia)
CAS No:	8016-65-7
EC No:	290-272-9
Registration No:	01-2120784901-47-0000

1.2 Relevant identified uses of the substance or mixture and uses advised against.

Industrial use.

Uses advised against:
Uses other than those recommended.

1.3 Details of the supplier of the safety data sheet.

Company:	**ESENCIAS MARTÍNEZ LOZANO, S.A.**
Address:	Carretera de Lorca, Km. 7
City:	30400 - Caravaca de la Cruz
Province:	Murcia (Spain)
Telephone:	+34 968725386
E-mail:	comercial@esenciaslozano.com
Web:	www.esenciaslozano.com

1.4 Emergency telephone number: +34 968725386 (Only available during office hours; Monday-Friday; 09:00-19:00)

SECTION 2: HAZARDS IDENTIFICATION.

2.1 Classification of the substance or mixture.

In accordance with Regulation (EC) No 1272/2008:

Aquatic Chronic 2 : Toxic to aquatic life with long lasting effects.
Asp. Tox. 1 : May be fatal if swallowed and enters airways.
Flam. Liq. 3 : Flammable liquid and vapour.
STOT SE 2 : May cause damage to organs.
Skin Irrit. 2 : Causes skin irritation.
Skin Sens. 1 : May cause an allergic skin reaction.

2.2 Label elements.

Labelling in accordance with Regulation (EC) No 1272/2008:

Pictograms:



Signal Word:

Danger

Hazard statements:

H226	Flammable liquid and vapour.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H371	May cause damage to organs.

-Continued on next page.-

H411 Toxic to aquatic life with long lasting effects.

Precautionary statements:

P210 Keep away from heat, hot surfaces, sparks, open flames and other ignition sources. No smoking.
P260 Do not breathe vapours.
P280 Wear protective gloves/protective clothing/eye protection/face protection/hearing protection/…
P301+P310 IF SWALLOWED: Immediately call a POISON CENTER/doctor.
P321 Specific treatment (see on MSDS).
P331 Do NOT induce vomiting.
P370+P378 In case of fire: Use foam or powder to extinguish.

2.3 Other hazards.

The substance is not PBT
The substance is not vPvB
Substance does not have endocrine disrupting properties.

In normal use conditions and in its original form, the product itself does not involve any other risk for health and the environment.

SECTION 3: COMPOSITION/INFORMATION ON INGREDIENTS.

3.1 Substances.
UVCB (Substance of Unknown or Variable composition, Complex reaction products or Biological materials).

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
CAS No: 8016-65-7 EC No: 290-272-9	Sage oil, Spanish (Salvia lavandifolia)		Acute Tox. 4, H332 - Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - STOT SE 2, H371 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-

Composition:

Identifiers	Name	Concentrate	(*)Classification - Regulation (EC) No 1272/2008	
			Classification	Specifics concentration limits and Acute toxicity estimate
CAS No: 76-22-2 EC No: 200-945-0	Camphor	10 - 25 %	Acute Tox. 4, H332 - Flam. Sol. 2, H228 - STOT SE 2, H371	-
CAS No: 470-82-6 EC No: 207-431-5	cineole	1 - 25 %	Flam. Liq. 3, H226 - Skin Sens. 1, H317	-
Index No: 603-235-00-2 CAS No: 78-70-6 EC No: 201-134-4	Linalool, 3,7-dimethyl- 1,6-octadien-3-ol, dl-linalool	1 - 10 %	Skin Sens. 1B, H317	-

-Continued on next page.-

CAS No: 127-91-3 EC No: 204-872-5	Pin-2(10)-ene	1 - 10 %	Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-
CAS No: 80-56-8 EC No: 201-291-9	alpha-Pinene	2.5 - 10 %	Acute Tox. 4, H302 - Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315 - Skin Sens. 1, H317	-
CAS No: 123-35-3 EC No: 204-622-5	7-methyl-3-methyleneocta-1,6-diene	1 - 10 %	Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315	-
Index No: 601-096-00-2 CAS No: 5989-27-5 EC No: 227-813-5	limonene (CAS:138-86-3 EINECS:205-341-0)	1 - 2.5 %	Aquatic Acute 1, H400 (M=1) - Aquatic Chronic 1, H410 - Asp. Tox. 1, H304 - Flam. Liq. 3, H226 - Skin Irrit. 2, H315 - Skin Sens. 1B, H317	-
CAS No: 507-70-0 EC No: 208-080-0	Borneol	0 - 2.5 %	Flam. Sol. 2, H228	-
CAS No: 562-74-3 EC No: 209-235-5	4-Terpinenol	1 - 10 %	Acute Tox. 4, H302 - Eye Irrit. 2, H319 - Skin Irrit. 2, H315	-
CAS No: 79-92-5 EC No: 201-234-8	Camphene	0.25 - 2.5 %	Aquatic Acute 1, H400 - Aquatic Chronic 1, H410 - Eye Irrit. 2, H319 - Flam. Sol. 2, H228	-
Index No: 603-241-00-5 CAS No: 106-24-1 EC No: 203-377-1	geraniol, (2E)-3,7-dimethylocta2,6-dien-1-ol	0.1 - 1 %	Skin Sens. 1, H317	-
Index No: 605-019-00-3 CAS No: 5392-40-5 EC No: 226-394-6	citral	0.1 - 1 %	Skin Irrit. 2, H315 - Skin Sens. 1, H317	-
CAS No: 115-95-7 EC No: 204-116-4	Linalyl acetate	0.1 - 1 %	Eye Irrit. 2, H319 - Skin Irrit. 2, H315 - Skin Sens. 1B, H317	-

-Continued on next page.-

CAS No: 3387-41-5 EC No: 222-212-4	thuj-4(10)-ene	0 - 2.5 %	Flam. Liq. 3, H226	-

(*) *The complete text of the H phrases is given in section 16 of this Safety Data Sheet.*

3.2 Mixtures.
Not Applicable.

SECTION 4: FIRST AID MEASURES.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.

4.1 Description of first aid measures.
In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious.

Inhalation.
Take the victim into open air; keep them warm and calm. If breathing is irregular or stops, perform artificial respiration. Do not administer anything orally. If unconscious, place them in a suitable position and seek medical assistance.

Eye contact.
Remove contact lenses, if present and if it is easy to do. Wash eyes with plenty of clean and cool water for at least 10 minutes while pulling eyelids up, and seek medical assistance.

Skin contact.
Remove contaminated clothing. Wash skin vigorously with water and soap or a suitable skin cleaner. NEVER use solvents or thinners.

Ingestion.
If accidentally ingested, seek immediate medical attention. Keep calm. NEVER induce vomiting.

4.2 Most important symptoms and effects, both acute and delayed.
Irritant Product, repeated or prolonged contact with skin or mucous membranes can cause redness, blisters or dermatitis, inhalation of spray mist or particles in suspension may cause irritation of the respiratory tract, some symptoms may not be immediate.
Harmful Product, prolonged exposure due to inhalation may cause anaesthetic effects and the need for immediate medical assistance.
It may cause an allergic reaction, dermatitis, redness or inflammation of the skin.

4.3 Indication of any immediate medical attention and special treatment needed.
In case of doubt or when symptoms of feeling unwell persist, get medical attention. Never administer anything orally to persons who are unconscious. Do not induce vomiting. If the person vomits, clear the respiratory tract.

SECTION 5: FIREFIGHTING MEASURES.

Flammable product, the necessary prevention measures should be taken in order to avoid risks, In case of fire, the following measures are recommended:

5.1 Extinguishing media.
Suitable extinguishing media:
Extinguisher powder or CO2. In case of more serious fires, also alcohol-resistant foam and water spray.

Unsuitable extinguishing media:
Do not use a direct stream of water to extinguish. In the presence of electrical voltage, you cannot use water or foam as extinguishing media.

5.2 Special hazards arising from the substance or mixture.
Special risks.
Exposure to combustion or decomposition products can be harmful to your health.

-Continued on next page.-

During a fire and depending on its magnitude the following may occur:
- Carbon monoxide, carbon dioxide.
- Flammable vapors or gases.

5.3 Advice for firefighters.
Use water to cool tanks, cisterns, or containers close to the heat source or fire. Take wind direction into account. Prevent the products used to fight the fire from going into drains, sewers, or waterways. Product residues and extinguishing media may contaminate the aquatic environment. Follow the instructions given in the emergency or fire evacuation plan or plans if available.

Fire protection equipment.
According to the size of the fire, it may be necessary to use protective suits against the heat, individual breathing equipment, gloves, protective goggles or facemasks, and boots. During extinction and depending on the magnitude and proximity to the fire, additional protective equipment such as chemical protection gloves, heat-reflecting suits or gas-tight suits may be required.

SECTION 6: ACCIDENTAL RELEASE MEASURES.

6.1 Personal precautions, protective equipment and emergency procedures.
Eliminate possible ignition points and ventilate the area. No smoking. Avoid breathing fumes. For exposure control and individual protection measures, see section 8.

6.2 Environmental precautions.
Product dangerous for the environment, in case of large spills or if the product contaminates lakes, rivers, or sewers, inform the responsible authorities according to local legislation. Prevent the contamination of drains, surface or subterranean waters, and the ground.

6.3 Methods and material for containment and cleaning up.
Contain and collect spillage with inert absorbent material (earth, sand, vermiculite, Kieselguhr...) and clean the area immediately with a suitable decontaminant.
Deposit waste in closed and suitable containers for disposal, in compliance with local and national regulations (see section 13).

6.4 Reference to other sections.
For exposure control and individual protection measures, see section 8.
For later elimination of waste, follow the recommendations under section 13.

SECTION 7: HANDLING AND STORAGE.

7.1 Precautions for safe handling.
The fumes are heavier than air and can spread across the ground. They can form explosive mixtures with air. Prevent the creation of flammable or explosive fume concentrations in the air; prevent fume concentrations above work exposure limits. The product must only be used in areas where all unprotected flames and other ignition points have been eliminated. Electrical equipment has to be protected according to applicable standards.
The product can be electrostatically charged: always use earth grounds when transferring the product. Operators must use anti-static footwear and clothing, and floors must be conductors.
Keep the container tightly closed and isolated from heat sources, sparks, and fire. Do not use tools that can cause sparks. For personal protection, see section 8.
In the application area, smoking, eating, and drinking must be prohibited.
Follow legislation on occupational health and safety.
Never use pressure to empty the containers. They are not pressure-resistant containers. Keep the product in containers made of a material identical to the original.

7.2 Conditions for safe storage, including any incompatibilities.
Store according to local legislation. Observe indications on the label. Store the containers between 5 and 25 º C, in a dry and well-ventilated place, far from sources of heat and direct solar light. Keep far away from ignition points. Keep away from oxidising agents and from highly acidic or alkaline materials. Do not smoke. Prevent the entry of non-authorised persons. Once the containers are open, they must be carefully closed and placed vertically to prevent spills.

The product is not affected by Directive 2012/18/EU (SEVESO III).

7.3 Specific end use(s).

-Continued on next page.-

Not available.

SECTION 8: EXPOSURE CONTROLS/PERSONAL PROTECTION.

8.1 Control parameters.

Work exposure limit for:

Name	CAS No.	Country	Limit value	ppm	mg/m³
Camphor	76-22-2	Éire [1]	**Eight hours**	2	12
			Short term	3	18
		United States [2] (Cal/OSHA)	**Eight hours**		2
			Short term		
		United States [3] (NIOSH)	**Eight hours**		2
			Short term		
		United States [4] (OSHA)	**Eight hours**		2
			Short term		
citral	5392-40-5	Éire [1]	**Eight hours**	5 (Inhalation fraction vapour)	
			Short term		

[1] According Code of Practice for the Safety, Health and Welfare at Work (Chemicals Agents) Regulations adopted by Health and Safety Authority (HSA).
[2] California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).
[3] National Institute for Occupational Safety and Health. NIOSH Recommendations for occupational safety and health, Compendium of Policy Documents and Statements, January, 1992, DHHS (NIOSH) Publication No. 92-100.
[4] Occupational Safety and Health Administration, United States Department of Labor. Permissible Exposure limits (PELs), California Division of Occupational Safety and Health (Cal/OSHA) Permissible Exposure Limits (PELs).
The product does NOT contain substances with Biological Limit Values.
Concentration levels DNEL/DMEL:

Name	DNEL/DMEL	Type	Value
Pin-2(10)-ene CAS No: 127-91-3 EC No: 204-872-5	DNEL (Workers)	Inhalation, Chronic, Systemic effects	5,98 (mg/m³)
alpha-Pinene CAS No: 80-56-8 EC No: 201-291-9	DNEL (Workers)	Inhalation, Chronic, Systemic effects	5,98 (mg/m³)
7-methyl-3-methyleneocta-1,6-diene CAS No: 123-35-3 EC No: 204-622-5	DNEL (Workers)	Inhalation, Chronic, Systemic effects	5,83 (mg/m³)
Camphene CAS No: 79-92-5 EC No: 201-234-8	DNEL (Workers)	Inhalation, Chronic, Systemic effects	110,19 (mg/m³)
citral CAS No: 5392-40-5 EC No: 226-394-6	DNEL (Workers)	Inhalation, Chronic, Systemic effects	9 (mg/m³)
Linalyl acetate CAS No: 115-95-7 EC No: 204-116-4	DNEL (Workers)	Inhalation, Chronic, Systemic effects	2,75 (mg/m³)

DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.

8.2 Exposure controls.

Measures of a technical nature:
Provide adequate ventilation, which can be achieved by using good local exhaust-ventilation and a good general exhaust system.

Concentration:	**100 %**

-Continued on next page.-

Uses:	**Industrial use.**
Breathing protection:	
PPE:	Filter mask for protection against gases and particles.
Characteristics:	«CE» marking, category III. The mask must have a wide field of vision and an anatomically designed form in order to be sealed and watertight.
CEN standards:	EN 136, EN 140, EN 405
Maintenance:	Should not be stored in places exposed to high temperatures and damp environments before use. Special attention should be paid to the state of the inhalation and exhalation valves in the face adaptor.
Observations:	Read carefully the manufacturer's instructions regarding the equipment's use and maintenance. Attach the necessary filters to the equipment according to the specific nature of the risk (Particles and aerosols: P1-P2-P3, Gases and vapours: A-B-E-K-AX), changing them as advised by the manufacturer.
Filter Type needed:	A2
Hand protection:	
PPE:	Protective gloves against chemicals.
Characteristics:	«CE» marking, category III.
CEN standards:	EN 374-1, En 374-2, EN 374-3, EN 420
Maintenance:	Keep in a dry place, away from any sources of heat, and avoid exposure to sunlight as much as possible. Do not make any changes to the gloves that may alter their resistance, or apply paints, solvents or adhesives.
Observations:	Gloves should be of the appropriate size and fit the user's hand well, not being too loose or too tight. Always use with clean, dry hands.

Material:	PVC (polyvinyl chloride)	Breakthrough time (min.):	> 480	Material thickness (mm):	0,35

Eye protection:	
PPE:	Protective goggles with built-in frame.
Characteristics:	«CE» marking, category II. Eye protector with built-in frame for protection against dust, smoke, fog and vapour.
CEN standards:	EN 165, EN 166, EN 167, EN 168
Maintenance:	Visibility through lenses should be ideal. Therefore, these parts should be cleaned daily. Protectors should be disinfected periodically following the manufacturer's instructions.
Observations:	Some signs of wear and tear include: yellow colouring of the lenses, superficial scratching of the lenses, scraping etc.
Skin protection:	
PPE:	Anti-static protective clothing.
Characteristics:	«CE» marking, category II. Protective clothing should not be too tight or loose in order not to obstruct the user's movements.
CEN standards:	EN 340, EN 1149-1, EN 1149-2, EN 1149-3, EN 1149-5
Maintenance:	In order to guarantee uniform protection, follow the washing and maintenance instructions provided by the manufacturer.
Observations:	The protective clothing should offer a level of comfort in line with the level of protection provided in terms of the hazard against which it protects, bearing in mind environmental conditions, the user's level of activity and the expected time of use.
PPE:	Anti-static safety footwear.
Characteristics:	«CE» marking, category II.
CEN standards:	EN ISO 13287, EN ISO 20344, EN ISO 20346
Maintenance:	The footwear should be checked regularly
Observations:	The level of comfort during use and acceptability are factors that are assessed very differently depending on the user. Therefore, it is advisable to try on different footwear models and, if possible, different widths.

SECTION 9: PHYSICAL AND CHEMICAL PROPERTIES.

9.1 Information on basic physical and chemical properties.
Physical state: Liquid
Colour: Not applicable/Not available due to the nature/properties of the product
Odour: Not applicable/Not available due to the nature/properties of the product
Odour threshold: Not applicable/Not available due to the nature/properties of the product
Melting point: Not applicable/Not available due to the nature/properties of the product
Freezing point: Not applicable/Not available due to the nature/properties of the product

-Continued on next page.-

Boiling point or initial boiling point and boiling range: 208 ºC (Estimation based on the indication of the Regulation (CE) Nº1272/2008.)
Flammability: Not applicable/Not available due to the nature/properties of the product
Lower explosion limit: Not applicable/Not available due to the nature/properties of the product
Upper explosion limit: Not applicable/Not available due to the nature/properties of the product
Flash point: 49 ºC
Auto-ignition temperature: Not applicable/Not available due to the nature/properties of the product
Decomposition temperature: Not applicable/Not available due to the nature/properties of the product
pH: Not applicable/Not available due to the nature/properties of the product
Kinematic viscosity: Not applicable/Not available due to the nature/properties of the product
Solubility: Not applicable/Not available due to the nature/properties of the product
Hydrosolubility: Not applicable/Not available due to the nature/properties of the product
Liposolubility: Not applicable/Not available due to the nature/properties of the product
Partition coefficient n-octanol/water (log value): Not applicable/Not available due to the nature/properties of the product
Vapour pressure: 0,979 (Estimation based on the indication of the Regulation (CE) Nº1272/2008.)
Absolute density: Not applicable/Not available due to the nature/properties of the product
Relative density: 0.907 - 0.932
Relative vapour density: Not applicable/Not available due to the nature/properties of the product
Particle characteristics: Not applicable/Not available due to the nature/properties of the product

9.2 Other information
Information with regard to physical hazard classes
Flammable liquids:
Sustained combustibility: Yes.

SECTION 10: STABILITY AND REACTIVITY.

10.1 Reactivity.
If the storage conditions are satisfied, does not produce dangerous reactions.

10.2 Chemical stability.
Stable under the recommended handling and storage conditions (see section 7).

10.3 Possibility of hazardous reactions.
Flammable liquid and vapour.

10.4 Conditions to avoid.
Avoid the following conditions:
- High temperature.
- Static discharge.
- Contact with incompatible materials.
- Avoid temperatures near or above the flash point. Do not heat closed containers. Avoid direct sunlight and heat, as these may cause a risk of fire.

10.5 Incompatible materials.
Avoid the following materials:
- Explosives materials.
- Toxic materials.
- Oxidizing materials.

10.6 Hazardous decomposition products.
In case of fire, dangerous decomposition products can be generated, such as carbon monoxide and dioxide and nitrogen fumes and oxides.

SECTION 11: TOXICOLOGICAL INFORMATION.

IRRITANT MIXTURE. Its repeated or prolonged contact with the skin or mucous membranes can cause irritant symptoms such as reddening of the skin, blisters, or dermatitis. Some of the symptoms may not be immediate. They can cause allergic reactions on the skin.
11.1 Information on hazard classes as defined in Regulation (EC) Nº 1272/2008.
There are no tested data available on the product.

-Continued on next page.-

Repeated or prolonged contact with the product can cause the elimination of oil from the skin, giving rise to non-allergic contact dermatitis and absorption of the product through the skin.

a) acute toxicity;
Not conclusive data for classification.

Acute Toxicity Estimate (ATE):
Substances:
ATE (Oral) = 4.052 mg/kg

b) skin corrosion/irritation;
Product classified:
Skin irritant, Category 2: Causes skin irritation.

c) serious eye damage/irritation;
Not conclusive data for classification.

d) respiratory or skin sensitisation;
Product classified:
Skin sensitiser, Category 1: May cause an allergic skin reaction.

e) germ cell mutagenicity;
Not conclusive data for classification.

f) carcinogenicity;
Not conclusive data for classification.

g) reproductive toxicity;
Not conclusive data for classification.

h) STOT-single exposure;
Product classified:
Specific target organ toxicity following a single exposure, Category 2: May cause damage to organs.

i) STOT-repeated exposure;
Not conclusive data for classification.

j) aspiration hazard;
Product classified:
Aspiration toxicity, Category 1: May be fatal if swallowed and enters airways.

11.2 Information on other hazards.
Endocrine disrupting properties
This product does not contain components with endocrine-disrupting properties with effects on human health.
Other information
There is no information available on other adverse health effects.

SECTION 12: ECOLOGICAL INFORMATION.

12.1 Toxicity.
No information is available regarding the ecotoxicity.

12.2 Persistence and degradability.
No information is available regarding the biodegradability
No information is available on the degradability
No information is available about persistence and degradability of the product.

12.3 Bioaccumulative potential.
Information about the bioaccumulation.

Name	Bioaccumulation

-Continued on next page.-

	Log Pow	BCF	NOECs	Level
Camphor CAS No: 76-22-2 EC No: 200-945-0	2,34	-	-	Low
Pin-2(10)-ene CAS No: 127-91-3 EC No: 204-872-5	4,16	-	-	High
alpha-Pinene CAS No: 80-56-8 EC No: 201-291-9	4,48	-	-	High
Camphene CAS No: 79-92-5 EC No: 201-234-8	4,22	-	-	High
Linalyl acetate CAS No: 115-95-7 EC No: 204-116-4	3,93	-	-	Moderate

12.4 Mobility in soil.
No information is available about the mobility in soil.
The product must not be allowed to go into sewers or waterways.
Prevent penetration into the ground.

12.5 Results of PBT and vPvB assessment.
No information is available about the results of PBT and vPvB assessment of the product.

12.6 Endocrine disrupting properties.
This product doesn't contain components with environmental endocrine disrupting properties.

12.7 Other adverse effects.
No information is available about other adverse effects for the environment.

SECTION 13: DISPOSAL CONSIDERATIONS.

13.1 Waste treatment methods.
Do not dump into sewers or waterways. Waste and empty containers must be handled and eliminated according to current, local/national legislation.
Follow the provisions of Directive 2008/98/EC regarding waste management.

SECTION 14: TRANSPORT INFORMATION.

Transport following ADR rules for road transport, RID rules for railway, ADN for inner waterways, IMDG for sea, and ICAO/IATA for air transport.
Land: Transport by road: ADR, Transport by rail: RID.
Transport documentation: Consignment note and written instructions
Sea: Transport by ship: IMDG.
Transport documentation: Bill of lading
Air: Transport by plane: ICAO/IATA.
Transport document: Airway bill.

-Continued on next page.-

14.1 UN number or ID number.
UN No: UN1197

14.2 UN proper shipping name.
Description:
ADR/RID: UN 1197, EXTRACTS, FLAVOURING, LIQUID, 3, PG III, (D/E)
IMDG: UN 1197, EXTRACTS, FLAVOURING, LIQUID (ALPHA-PINENE), 3, PG III (49ºC), MARINE POLLUTANT
ICAO/IATA: UN 1197, EXTRACTS, FLAVOURING, LIQUID, 3, PG III

14.3 Transport hazard class(es).
Class(es): 3

14.4 Packing group.
Packing group: III

14.5 Environmental hazards.
Marine pollutant: Yes



Dangerous for the environment
Transport by ship, FEm – Emergency sheets (F – Fire, S - Spills): F-E,S-D

14.6 Special precautions for user.
Labels: 3



Hazard number: 30
ADR LQ: 5 L
IMDG LQ: 5 L
ICAO LQ: 10 L

Provisions concerning carriage in bulk ADR: Not authorized carriage in bulk in accordance with ADR.
Proceed in accordance with point 6.

14.7 Maritime transport in bulk according to IMO instruments.
The product is not transported in bulk.

SECTION 15: REGULATORY INFORMATION.

15.1 Safety, health and environmental regulations/legislation specific for the substance or mixture.
The product is not affected by the Regulation (EC) No 1005/2009 of the European Parliament and of the Council of 16 September 2009 on substances that deplete the ozone layer.

Product classification according to Annex I of Directive 2012/18/EU (SEVESO III): N/A
The product is not affected by Regulation (EU) No 528/2012 concerning the making available on the market and use of biocidal products.
The product is not affected by the procedure established Regulation (EU) No 649/2012, concerning the export and import of dangerous chemicals.

15.2 Chemical safety assessment.

-Continued on next page.-

No Chemical Safety Assessment has been carried out for this substance/mixture by the supplier.

SECTION 16: OTHER INFORMATION.

Complete text of the H phrases that appear in section 3:

H226	Flammable liquid and vapour.
H228	Flammable solid.
H302	Harmful if swallowed.
H304	May be fatal if swallowed and enters airways.
H315	Causes skin irritation.
H317	May cause an allergic skin reaction.
H319	Causes serious eye irritation.
H332	Harmful if inhaled.
H371	May cause damage to organs.
H400	Very toxic to aquatic life.
H410	Very toxic to aquatic life with long lasting effects.

Classification codes:

Acute Tox. 4 : Acute toxicity (Inhalation), Category 4
Acute Tox. 4 : Acute toxicity (Oral), Category 4
Aquatic Acute 1 : Acute toxicity to the aquatic environment, Category 1
Aquatic Chronic 1 : Chronic effect to the aquatic environment, Category 1
Aquatic Chronic 2 : Chronic effect to the aquatic environment, Category 2
Asp. Tox. 1 : Aspiration toxicity, Category 1
Eye Irrit. 2 : Eye irritation, Category 2
Flam. Liq. 3 : Flammable liquid, Category 3
Flam. Sol. 2 : Flammable solid, Category 2
STOT SE 2 : Specific target organ toxicity following a single exposure, Category 2
Skin Irrit. 2 : Skin irritant, Category 2
Skin Sens. 1 : Skin sensitiser, Category 1
Skin Sens. 1B : Skin sensitiser, Category 1B

Changes regarding to the previous version:

- Modification of exposure data (SECTION 8.1).
- Modification in the values of the physical and chemical properties (SECTION 9).
- Modification of the classification ADR/IMDG/ICAO/IATA/RID (SECTION 14).

Classification and procedure used to derive the classification for mixtures according to Regulation (EC) 1272/2008 [CLP]:

Physical hazards	On basis of test data
Health hazards	Calculation method
Environmental hazards	Calculation method

It is advisable to carry out basic training with regard to health and safety at work in order to handle this product correctly.

Abbreviations and acronyms used:
ADR/RID: European Agreement concerning the International Carriage of Dangerous Goods by Road.
BCF: Bioconcentration factor.
CEN: European Committee for Standardization.
DMEL: Derived Minimal Effect Level, exposure level corresponding to a low risk, that risk should be considered a tolerable minimum.
DNEL: Derived No Effect Level, level of exposure to the substance below which adverse effects are not anticipated.
EC50: Half maximal effective concentration.

-Continued on next page.-

PPE: Personal protection equipment.
IATA: International Air Transport Association.
ICAO: International Civil Aviation Organization.
IMDG: International Maritime Code for Dangerous Goods.
LC50: Lethal concentration, 50%.
LD50: Lethal dose, 50%.
NOEC: No observed effect concentration.
RID: Regulations Concerning the International Transport of Dangerous Goods by Rail.

Key literature references and sources for data:
http://eur-lex.europa.eu/homepage.html
http://echa.europa.eu/
Regulation (EU) 2020/878.
Regulation (EC) No 1907/2006.
Regulation (EC) No 1272/2008.

The information given in this Safety Data Sheet has been drafted in accordance with COMMISSION REGULATION (EU) 2020/878 of 18 June 2020 amending Annex II to Regulation (EC) No 1907/2006 of the European Parliament and of the Council on the Registration, Evaluation, Authorisation and Restriction of Chemical substances and mixtures (REACH).

The information in this Safety Data Sheet on the Preparation is based on current knowledge and on current EC and national laws, as far as the working conditions of the users is beyond our knowledge and control. The product must not be used for purposes other than those that are specified without first having written instructions on how to handle. It is always the responsibility of the user to take the appropriate measures in order to comply with the requirements established by current legislation. The information contained in this Safety Sheet only states a description of the safety requirements for the preparation, and it must not be considered as a guarantee of its properties.

-End of safety data sheet.-